



Date of issue 2021-02-01

Version 1.0

Total pages 39

Test report of

IES LM-79-08

Approved Method: Electrical and Photometric

Measurements of Solid-State Lighting Products

Applicant:

LIGHT EFFICIENT DESIGN

Address:

188 S. Northwest Highway Cary, IL 60013 USA

For Product:

Linear Replacement Lamps -- 4' T5 Lamps--4-lamp External Driver (UL Type C)
Lamps

Product Model No.:

RP-T5C-G2-30W-4FT-4L-830-[OCN, Blank]-10V,
RP-T5C-G2-30W-4FT-4L-850-[OCN, Blank]-10V,
RP-T5C-G2-35W-4FT-4L-830-[OCN, Blank]-10V,
RP-T5C-G2-35W-4FT-4L-850-[OCN, Blank]-10V,
RP-T5C-G2-40W-4FT-4L-830-[OCN, Blank]-10V,
RP-T5C-G2-40W-4FT-4L-850-[OCN, Blank]-10V,
RP-T5C-G2-45W-4FT-4L-830-[OCN, Blank]-10V,
RP-T5C-G2-45W-4FT-4L-850-[OCN, Blank]-10V

Test laboratory: Shenzhen Belling Efficiency Testing Lab Co.,Ltd, 1Floor, No.1 Building, Meibaohe Industrial Park, Dalang Street, Longhua District, Shenzhen, Guangdong Prov.518101 China.

Jarvis zhang

Jason zhou

Complied by: Jarvis zhang

Review by: Jason zhou

Project Engineer

Technical Manager

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or use in part without prior written consent from Shenzhen Belling Efficiency Testing Lab Co.,Ltd. This report must not be used by the customer to claim product certification, approval, or endorsement By NVLAP, NIST, or any agency of the U.S. Government.



1 General

1.1 Product Information

Manufacturer	LIGHT EFFICIENT DESIGN
Manufacturer Address	188 S. Northwest Highway Cary, IL 60013 USA
Brand Name	REMPHOS OR LIGHT EFFICIENT DESIGN
Luminaire Type	Linear Replacement Lamps -- 4' T5 Lamps--4-lamp External Driver (UL Type C) Lamps
Test Model Number	RP-T5C-G2-30W-4FT-4L-830-[OCN, Blank]-10V, RP-T5C-G2-30W-4FT-4L-850-[OCN, Blank]-10V, RP-T5C-G2-35W-4FT-4L-830-[OCN, Blank]-10V, RP-T5C-G2-35W-4FT-4L-850-[OCN, Blank]-10V, RP-T5C-G2-40W-4FT-4L-830-[OCN, Blank]-10V, RP-T5C-G2-40W-4FT-4L-850-[OCN, Blank]-10V, RP-T5C-G2-45W-4FT-4L-830-[OCN, Blank]-10V, RP-T5C-G2-45W-4FT-4L-850-[OCN, Blank]-10V
Rated Inputs	AC 100-277V 50/60Hz
Field-Adjustable Product	Yes, Wattage setting: 30W, 35W, 40W, 45W
Nominal CCT	3000K, 5000K
Dimming Capability	Continuous
Integral Control Sensors	Optional
Date of Receipt Samples	2020-12-21
Date of test	2020-12-22 to 2021-01-21
Burning Time Before Test	0hour(For New Products)

1.2 Standards or methods

- ANSI C78.377-2017:Specifications for the Chromaticity of Solid State Lighting Products
- ANSI C82.77-10:2014:Harmonic Emission Limits - Related Power Quality Requirements for Lighting Equipment - Solid State
- CIE Publication No.13.3-1995:Method of Measuring and Specifying Color Rendering of Light Sources
- IESNA LM-79-08 Approved Method: Electric & Photometric Measurement of Solid-state Lighting Products



1.3 Equipment list

Device	Manufacture	Model No.	Serial No.	Calibration due date
Goniophotometric System	SENSING	GMS-3000	N.A	2021-04-02
AC Power Source	ALL POWER	APW-110N	992257	2021-04-02
Total Luminous Flux Standard Lamp	SENSING	110V/100W	S1510065	2021-04-08
Total Spectral Radiant Flux Standard Lamp	SENSING	12V/20W	LSD12201731	2021-04-08
Digital Power Meter	YOKOGAWA	WT310	C2QM02030V	2021-04-02
Integral Sphere	SENSING	SPR-600M	N.A	2021-04-02
Digital Power Meter	YOKOGAWA	WT210	91L929742	2021-04-02
Optical Color and Electrical Measurement System	SENSING	SPR-3000	S1101108	2021-04-02
Environment Measurer	XUYAO	HS-1	N/A	2021-04-08
Environment Measurer	XUYAO	HS-1	N/A	2021-04-08
Stop watch	KISLO	K610	N/A	2021-04-27
Digital Anemometer	TECMAN	TD8901	026141	2021-09-09

Statement of Traceability: Shenzhen Belling Efficiency Testing Lab Co.,Ltd attests that all calibration has been performed using suitable standards traceable to national primary standards and International System of Unit (SI).



2 Test conducted and method

2.1 Ambient Condition

The ambient temperature in which measurements are being taken was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, the air flow around the sample(s) being tested did not affect the performance.

2.2 Power Supply Characteristics

The AC power supply had a sinusoidal voltage wave shape at the prescribed frequency (60 Hz) such that the RMS summation of the harmonic components does not exceed 3 percent of the fundamental during operation of the test item.

The voltage of AC power supply (RMS voltage) applied to the device under test was regulated to within ± 0.2 percent under load.

2.3 Seasoning and Stabilization

No seasoning was performed in accordance with IESNA LM-79-08. And before the measurement, the sample was stabilized until the light output and power variations were less than 0.5% in 30 minutes intervals (3 readings, 15 minutes apart).

2.4 Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, spectrophotometer, and integrating sphere. The integrating sphere system is calibrated by standard light source before measurement. The system and standard light source has been calibrated regularly and traceable to the National Primary Standards. 4π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

Integrating Sphere Uncertainty: The uncertainty of the light output (luminous flux) measurements is $U=1.8\%$ ($K=2$), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is $U=20\text{K}$ ($K=2$), at the 95% confidence level. The uncertainty of the CRI is $U=1.8(K=2)$, at the 95% confidence level. The uncertainty of power meter AC current $U=0.18\%$ of rdg, AC Voltage $U=0.16\%$ of rdg, Power $U=0.20\%$ ($K=2$), at the 95% confidence level.



2.5 Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement. The standard light source has been calibrated regularly and traceable to the National Primary Standards.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The method according to IESNA LM-79-08 following chapter.

Goniophotometer Uncertainty :The uncertainty of the luminous intensity is $U=1.6\%$ ($K=2$), at the 95% confidence level.



3 Test Result Summary

3.1 Integrating Sphere System (Total operating time for integrating sphere test: 1.0 hour)

3.1.1 Model Number: RP-T5C-G2-30W-4FT-4L-830-[OCN, Blank]-10V

Electrical data

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.01	60	0.064	7.62	0.996

Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1098.08	144.2	2993


Chromaticity Coordinate

Duv	x	y	u'	v'
-0.00135	0.4355	0.4002	0.2513	0.5196

Color Rendering


CRI	R9	Rf	Rg	Rcs,h1(%)
84.0	13	85	97	-11

Spectral Distribution





7/4 Step Quadrangle






ANSI/IES TM-30-18 Color Rendition Report

Source: BL210201007-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2021/2/1

Model: RP-T5C-G2-30W-4FT-4L-S30-[OCN, Blank]-10V



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4355
 y 0.4002
 u' 0.2513
 v' 0.5196

CIE 13.3-1995
(CRI)

R_a 84
 R_g 12

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

**3.1.2 Model Number: RP-T5C-G2-30W-4FT-4L-850-[OCN, Blank]-10V****Electrical data**

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.00	60	0.064	7.69	0.996

Photometric data


Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1142.73	148.6	5002

Chromaticity Coordinate

Duv	x	y	u'	v'
+0.00226	0.3455	0.3564	0.2098	0.4871


Color Rendering

CRI	R9	Rf	Rg	Rcs,h1(%)
84.2	12	83	93	-12

Spectral Distribution



7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210201007-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2021/2/1

Model: RP-T5C-G2-30W-4FT-4L-850-[OCN, Blank]-10V



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

 x 0.3455 y 0.3564 u' 0.2098 v' 0.4871CIE 13.3-1995
(CRI) R_a 84 R_g 12

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.



3.1.3 Model Number: RP-T5C-G2-35W-4FT-4L-830-[OCN, Blank]-10V

Electrical data

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
119.98	60	0.073	8.76	0.996

Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1205.56	137.7	2998


Chromaticity Coordinate

Duv	x	y	u'	v'
-0.00133	0.4352	0.4002	0.2511	0.5196

Color Rendering


CRI	R9	Rf	Rg	Rcs,h1(%)
84.0	13	85	97	-11

Spectral Distribution





7/4 Step Quadrangle






ANSI/IES TM-30-18 Color Rendition Report

Source: BL210201007-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2021/2/1

Model: RP-T5C-G2-35W-4FT-4L-830-[OCN, Blank]-10V



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

 x 0.4352 y 0.4002 u' 0.2511 v' 0.5196CIE 13.3-1995
(CRI) R_a 84 R_g 13

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

**3.1.4 Model Number: RP-T5C-G2-35W-4FT-4L-850-[OCN, Blank]-10V****Electrical data**

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
119.96	60	0.074	8.80	0.996

Photometric data


Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1267.36	144.1	4997

Chromaticity Coordinate

Duv	x	y	u'	v'
+0.00229	0.3457	0.3566	0.2099	0.4872


Color Rendering

CRI	R9	Rf	Rg	Rcs,h1(%)
83.9	14	83	93	-12

Spectral Distribution



7/4 Step Quadrangle






ANSI/IES TM-30-18 Color Rendition Report

Source: BL210201007-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2021/2/1

Model: RP-T5C-G2-35W-4FT-4L-850-[OCN, Blank]-10V



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

 x 0.3457 y 0.3566 u' 0.2099 v' 0.4872

CIE 13.3-1995
(CRI)

 R_a 84 R_g 14

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

**3.1.5 Model Number: RP-T5C-G2-40W-4FT-4L-830-[OCN, Blank]-10V****Electrical data**

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
119.94	60	0.082	9.82	0.996

Photometric data


Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1347.65	137.2	2998

Chromaticity Coordinate

Duv	x	y	u'	v'
-0.00126	0.4353	0.4004	0.2511	0.5197


Color Rendering

CRI	R9	Rf	Rg	Rcs,h1(%)
83.9	12	85	97	-11

Spectral Distribution



7/4 Step Quadrangle






ANSI/IES TM-30-18 Color Rendition Report

Source: BL210201007-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2021/2/1

Model: RP-T5C-G2-40W-4FT-4L-S30-[OCN, Blank]-10V



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4353
 y 0.4004
 u' 0.2511
 v' 0.5197

CIE 13.3-1995
(CRI)

R_a 84
 R_9 12

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

**3.1.6 Model Number: RP-T5C-G2-40W-4FT-4L-850-[OCN, Blank]-10V****Electrical data**

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
119.94	60	0.083	9.91	0.996

Photometric data


Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1421.09	143.4	4996

Chromaticity Coordinate

Duv	x	y	u'	v'
+0.00215	0.3457	0.3564	0.21	0.4871


Color Rendering

CRI	R9	Rf	Rg	Rcs,h1(%)
84.0	14	83	93	-12

Spectral Distribution



7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210201007-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2021/2/1

Model: RP-T5C-G2-40W-4FT-4L-850-[OCN, Blank]-10V



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

 x 0.3457 y 0.3564 u' 0.2100 v' 0.4871CIE 13.3-1995
(CRI) R_a 84 R_g 14

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

**3.1.7 Model Number: RP-T5C-G2-45W-4FT-4L-830-[OCN, Blank]-10V****Electrical data**

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
119.90	60	0.091	10.82	0.996

Photometric data


Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1450.29	134.1	2989

Chromaticity Coordinate

Duv	x	y	u'	v'
-0.00085	0.4365	0.4018	0.2513	0.5204


Color Rendering

CRI	R9	Rf	Rg	Rcs,h1(%)
84.1	13	85	97	-11

Spectral Distribution



7/4 Step Quadrangle






ANSI/IES TM-30-18 Color Rendition Report

Source: BL210201007-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2021/2/1

Model: RP-T5C-G2-45W-4FT-4L-830-[OCN, Blank]-10V



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4365
 y 0.4018
 u' 0.2513
 v' 0.5204

CIE 13.3-1995
(CRI)

R_a 84
 R_g 12

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

**3.1.8 Model Number: RP-T5C-G2-45W-4FT-4L-850-[OCN, Blank]-10V****Electrical data**

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
119.91	60	0.090	10.75	0.996

Photometric data


Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1511.80	140.6	4993

Chromaticity Coordinate

Duv	x	y	u'	v'
+0.00216	0.3457	0.3565	0.21	0.4871


Color Rendering

CRI	R9	Rf	Rg	Rcs,h1(%)
83.9	14	83	93	-12

Spectral Distribution



7/4 Step Quadrangle






ANSI/IES TM-30-18 Color Rendition Report

Source: BL210201007-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2021/2/1

Model: RP-T5C-G2-45W-4FT-4L-850-[OCN, Blank]-10V



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

 x 0.3457 y 0.3565 u' 0.2100 v' 0.4871CIE 13.3-1995
(CRI) R_a

84

 R_g

13

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.



3.2 Goniophotometer System (Total operating time for luminous intensity distribution: 1.0 hour)

3.2.1 Model Number: RP-T5C-G2-45W-4FT-4L-830-[OCN, Blank]-10V

Electrical data

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.06	60	0.090	10.79	0.9956

Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	Beam Angle (°)
1456.77	135.01	188.2

**Zonal Flux Diagram**


Zonal flux distribution table

$\gamma(^{\circ})$	Average I(cd)	Zonal F(lm)	Sum F(lm)	Eff Flux(%)	Eff Sum(%)
0.0	287.489	0.000	0	0.00%	0.00%
5.0	286.729	6.865	6.865	0.00%	0.47%
10.0	283.713	20.408	27.272	0.00%	1.87%
15.0	278.508	33.354	60.626	0.00%	4.16%
20.0	270.664	45.265	105.891	0.00%	7.27%
25.0	260.338	55.703	161.594	0.00%	11.09%
30.0	248.654	64.428	226.021	0.00%	15.52%
35.0	236.390	71.443	297.464	0.00%	20.42%
40.0	224.485	76.916	374.381	0.00%	25.70%
45.0	211.505	80.764	455.145	0.00%	31.24%
50.0	197.541	82.706	537.851	0.00%	36.92%
55.0	183.712	82.952	620.802	0.00%	42.61%
60.0	169.286	81.649	702.451	0.00%	48.22%
65.0	155.110	78.922	781.374	0.00%	53.64%
70.0	140.568	74.940	856.314	0.00%	58.78%
75.0	126.580	69.901	926.215	0.00%	63.58%
80.0	113.133	64.219	990.434	0.00%	67.99%
85.0	101.252	58.331	1048.766	0.00%	71.99%
90.0	91.282	52.751	1101.516	0.00%	75.61%
95.0	83.319	47.803	1149.319	0.00%	78.89%
100.0	75.974	43.266	1192.586	0.00%	81.86%
105.0	69.516	38.908	1231.493	0.00%	84.54%
110.0	63.683	34.795	1266.289	0.00%	86.92%
115.0	58.448	30.901	1297.19	0.00%	89.05%
120.0	51.971	26.817	1324.006	0.00%	90.89%
125.0	48.071	23.098	1347.104	0.00%	92.47%
130.0	45.423	20.305	1367.409	0.00%	93.87%
135.0	43.283	17.901	1385.311	0.00%	95.09%
140.0	41.706	15.711	1401.022	0.00%	96.17%
145.0	40.370	13.669	1414.69	0.00%	97.11%
150.0	39.089	11.679	1426.369	0.00%	97.91%
155.0	37.392	9.660	1436.029	0.00%	98.58%
160.0	35.933	7.672	1443.7	0.00%	99.10%
165.0	34.723	5.810	1449.51	0.00%	99.50%
170.0	33.429	4.033	1453.544	0.00%	99.78%
175.0	34.050	2.406	1455.95	0.00%	99.94%
180.0	34.897	0.823	1456.773	0.00%	100.00%




Luminous Intensity Distribution Diagram

Light Distribution Curve [Unit:cd]





Lux distance Curve



Max , Ave

Beam angle of C247.5 plane 176.54

**Luminous Intensity Distribution Data**

C/γ(°)	0.0	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0
0.0	287.49	286.11	281.30	274.19	263.88	251.04	236.59	220.32	201.75
22.5	287.49	286.09	281.44	274.92	266.07	254.43	240.23	223.01	203.22
45.0	287.49	286.07	282.74	277.76	269.68	256.39	241.20	225.77	214.37
67.5	287.49	288.46	287.25	283.85	272.92	259.57	248.15	241.11	237.23
90.0	287.49	286.24	282.01	274.54	265.07	255.35	246.88	242.65	240.90
112.5	287.49	286.76	283.61	278.77	268.84	254.31	241.71	233.00	227.18
135.0	287.49	286.02	282.83	277.43	269.58	256.83	241.13	224.20	209.73
157.5	287.49	285.53	280.89	274.04	264.75	253.02	238.60	221.00	201.93
180.0	287.49	286.34	282.22	274.88	265.25	252.87	238.43	222.15	204.27
202.5	287.49	286.56	282.14	275.85	267.24	255.83	242.33	227.43	212.77
225.0	287.49	287.01	284.17	279.89	273.25	264.94	255.20	243.81	231.70
247.5	287.49	289.92	288.22	284.82	280.93	275.59	268.55	261.02	252.04
270.0	287.49	286.74	285.00	283.25	280.51	277.28	269.80	261.08	255.85
292.5	287.49	285.55	287.01	284.34	279.98	274.65	267.87	260.12	251.16
315.0	287.49	287.24	285.04	280.38	273.75	265.17	255.85	244.56	232.54
337.5	287.49	287.00	283.58	277.22	268.91	258.15	245.93	231.02	215.13
360.0	287.49	286.11	281.30	274.19	263.88	251.04	236.59	220.32	201.75
C/γ(°)	45.0	50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0
0.0	181.57	160.48	138.93	115.78	93.08	68.78	46.54	24.30	8.02
22.5	181.34	158.76	139.90	125.70	113.37	98.70	83.80	70.30	58.43
45.0	204.64	196.09	185.65	173.06	159.53	146.95	134.13	122.50	112.76
67.5	230.91	222.17	213.67	204.21	193.52	182.35	172.64	160.50	150.54
90.0	236.92	229.44	222.72	213.00	201.29	190.83	181.36	170.15	160.19
112.5	220.40	213.62	205.87	195.45	184.80	174.87	164.94	153.80	142.66
135.0	198.45	188.14	177.84	166.31	153.56	140.31	127.56	116.52	106.95
157.5	181.15	158.17	136.66	118.81	104.88	89.47	74.07	60.63	50.12
180.0	185.47	164.84	142.60	119.67	97.21	73.82	50.44	29.80	11.69
202.5	194.61	176.22	158.53	140.60	121.98	103.82	87.29	72.40	59.59
225.0	218.64	204.40	191.11	177.34	164.04	151.70	138.40	126.53	115.14
247.5	242.33	231.89	221.44	210.03	200.32	188.18	177.01	164.87	153.21
270.0	248.63	239.16	229.94	219.73	208.77	198.05	187.34	176.63	164.42
292.5	241.47	231.06	221.13	210.47	198.36	186.01	174.38	162.52	151.62
315.0	219.79	207.03	193.79	178.82	166.07	151.84	138.84	126.33	115.05
337.5	197.77	179.19	159.64	139.59	121.01	103.41	86.54	72.36	59.65
360.0	181.57	160.48	138.93	115.78	93.08	68.78	46.54	24.30	8.02
C/γ(°)	90.0	95.0	100.0	105.0	110.0	115.0	120.0	125.0	130.0
0.0	2.06	2.29	3.67	5.04	6.88	8.71	10.55	12.38	14.21
22.5	49.12	40.97	36.08	32.59	30.03	29.10	29.10	28.63	29.10
45.0	102.08	92.35	83.33	75.49	68.85	60.77	51.75	47.95	46.29
67.5	139.13	128.69	117.52	107.08	98.10	89.60	75.03	68.72	63.13
90.0	150.22	140.01	129.54	119.08	108.87	99.40	88.44	78.97	72.25
112.5	136.12	125.22	113.83	104.15	94.94	86.71	72.90	66.36	61.76
135.0	98.36	88.31	79.48	72.36	65.74	59.12	51.02	47.34	45.63
157.5	42.78	35.94	31.78	27.87	26.65	26.16	26.65	26.16	27.38
180.0	2.29	1.61	2.29	3.90	5.50	7.11	8.71	10.55	12.61
202.5	49.35	43.07	37.25	33.06	29.80	27.93	26.07	24.68	26.31
225.0	103.27	94.72	86.41	77.15	70.98	61.72	55.31	50.80	47.48
247.5	141.32	132.09	121.65	112.91	101.98	93.24	81.59	74.79	67.50
270.0	153.71	143.75	132.78	122.57	110.86	102.64	90.18	81.96	73.74
292.5	139.26	129.33	119.89	110.44	100.27	91.55	78.47	72.18	65.88
315.0	103.27	94.44	85.36	77.76	70.89	64.51	58.63	50.04	47.10
337.5	48.16	40.34	34.71	30.80	28.60	26.89	27.14	27.62	26.40
360.0	2.06	2.29	3.67	5.04	6.88	8.71	10.55	12.38	14.21



C/γ(°)	135.0	140.0	145.0	150.0	155.0	160.0	165.0	170.0	175.0
0.0	16.05	17.65	19.03	20.18	21.09	23.16	25.68	31.18	38.29
22.5	30.50	31.89	32.82	33.75	35.62	36.31	35.62	31.89	35.15
45.0	44.16	42.49	41.78	41.07	40.36	39.65	39.17	34.90	34.42
67.5	57.55	53.66	50.51	47.59	44.92	42.98	41.76	41.04	30.84
90.0	66.52	62.03	57.55	53.81	49.58	46.09	43.35	42.10	30.39
112.5	57.40	53.77	51.10	49.17	46.26	41.17	34.15	25.43	30.03
135.0	43.66	42.44	41.46	40.47	35.81	30.17	27.23	28.21	36.06
157.5	29.09	30.56	30.56	29.34	27.14	27.87	27.14	31.05	37.89
180.0	13.99	15.36	16.51	17.88	18.57	19.95	23.84	27.97	34.39
202.5	27.93	29.80	31.66	30.73	27.70	27.93	27.93	28.40	33.29
225.0	43.44	41.07	40.12	40.36	37.98	32.05	29.91	27.54	31.10
247.5	61.92	57.79	52.93	49.05	46.38	43.95	38.12	29.87	22.82
270.0	67.76	62.03	55.80	51.57	48.83	45.84	44.10	42.60	41.60
292.5	60.55	54.98	51.10	47.23	44.32	42.63	41.42	41.17	40.21
315.0	44.89	42.68	41.70	40.23	39.25	39.00	39.00	39.00	34.83
337.5	27.14	29.09	31.29	33.00	34.47	36.18	37.16	32.51	33.49
360.0	16.05	17.65	19.03	20.18	21.09	23.16	25.68	31.18	38.29
C/γ(°)	180.0								
0.0	42.41								
22.5	39.11								
45.0	37.51								
67.5	35.94								
90.0	11.46								
112.5	34.63								
135.0	38.51								
157.5	39.60								
180.0	42.41								
202.5	39.11								
225.0	37.51								
247.5	35.94								
270.0	11.46								
292.5	34.63								
315.0	38.51								
337.5	39.60								
360.0	42.41								



4 Additional Test

Electrical data at 277V

Model Number	Test Item	Test Voltage (V)	Frequency (Hz)	Test Result
RP-T5C-G2-45W-4FT-4L-830-[OCN, Blank]-10V	Power Factor	277	60	0.971
	THD	277	60	6.2%
RP-T5C-G2-45W-4FT-4L-850-[OCN, Blank]-10V	Power Factor	277	60	0.975
	THD	277	60	5.4%

5 Performance Assessment

Model name	CCT(K)	Total Luminous(lm)	Power(W)	Luminous Efficacy(lm/W)
RP-T5C-G2-30W-4FT-4L-830-[OCN, Blank]-10V	3000K	1098.08	7.62	144.2
RP-T5C-G2-30W-4FT-4L-835-[OCN, Blank]-10V	3500K	1109.24 ^{*1}	7.66 ^{*2}	144.9 ^{*3}
RP-T5C-G2-30W-4FT-4L-840-[OCN, Blank]-10V	4000K	1120.41 ^{*1}	7.66 ^{*2}	146.4 ^{*3}
RP-T5C-G2-30W-4FT-4L-850-[OCN, Blank]-10V	5000K	1142.73	7.69	148.6

*1: This value is calculated and the calculation formula is as below:

$$1109.24 = (1142.73 - 1098.08) / 4 + 1098.08$$

$$1120.41 = (1142.73 - 1098.08) / 4 + 1109.24$$

*2: This value is calculated and the calculation formula is as below:

$$7.66 = (7.62 + 7.69) / 2$$

*3: This value is calculated and the calculation formula is as below:

$$144.9 = 1109.24 / 7.66$$

$$146.4 = 1120.41 / 7.66$$



Model name	CCT(K)	Total Luminous(lm)	Power(W)	Luminous Efficacy(lm/W)
RP-T5C-G2-35W-4FT-4L -830-[OCN, Blank]-10V	3000K	1205.56	8.76	137.7
RP-T5C-G2-35W-4FT-4L -835-[OCN, Blank]-10V	3500K	1221.01 ^{*1}	8.78 ^{*2}	139.1 ^{*3}
RP-T5C-G2-35W-4FT-4L -840-[OCN, Blank]-10V	4000K	1236.46 ^{*1}	8.78 ^{*2}	140.8 ^{*3}
RP-T5C-G2-35W-4FT-4L -850-[OCN, Blank]-10V	5000K	1267.36	8.80	144.1

*1: This value is calculated and the calculation formula is as below:

$$1221.01 = (1267.36 - 1205.56) / 4 + 1205.56$$

$$1236.46 = (1267.36 - 1205.56) / 4 + 1221.01$$

*2: This value is calculated and the calculation formula is as below:

$$8.78 = (8.76 + 8.80) / 2$$

*3: This value is calculated and the calculation formula is as below:

$$139.1 = 1221.01 / 8.78$$

$$140.8 = 1236.46 / 8.78$$

Model name	CCT(K)	Total Luminous(lm)	Power(W)	Luminous Efficacy(lm/W)
RP-T5C-G2-40W-4FT-4L -830-[OCN, Blank]-10V	3000K	1347.65	9.82	137.2
RP-T5C-G2-40W-4FT-4L -835-[OCN, Blank]-10V	3500K	1366.01 ^{*1}	9.87 ^{*2}	138.5 ^{*3}
RP-T5C-G2-40W-4FT-4L -840-[OCN, Blank]-10V	4000K	1384.37 ^{*1}	9.87 ^{*2}	140.3 ^{*3}
RP-T5C-G2-40W-4FT-4L -850-[OCN, Blank]-10V	5000K	1421.09	9.91	143.4

*1: This value is calculated and the calculation formula is as below:

$$1366.01 = (1421.09 - 1347.65) / 4 + 1347.65$$

$$1384.37 = (1421.09 - 1347.65) / 4 + 1366.01$$

*2: This value is calculated and the calculation formula is as below:

$$9.87 = (9.82 + 9.91) / 2$$

*3: This value is calculated and the calculation formula is as below:

$$138.5 = 1366.01 / 9.87$$

$$140.3 = 1384.37 / 9.87$$



Model name	CCT(K)	Total Luminous(lm)	Power(W)	Luminous Efficacy(lm/W)
RP-T5C-G2-45W-4FT-4L -830-[OCN, Blank]-10V	3000K	1450.29	10.82	134.1
RP-T5C-G2-45W-4FT-4L -835-[OCN, Blank]-10V	3500K	1465.67 ^{*1}	10.79 ^{*2}	135.9 ^{*3}
RP-T5C-G2-45W-4FT-4L -840-[OCN, Blank]-10V	4000K	1481.05 ^{*1}	10.79 ^{*2}	137.3 ^{*3}
RP-T5C-G2-45W-4FT-4L -850-[OCN, Blank]-10V	5000K	1511.80	10.75	140.6

*1: This value is calculated and the calculation formula is as below:

$$1465.67 = (1511.80 - 1450.29) / 4 + 1450.29$$

$$1481.05 = (1511.80 - 1450.29) / 4 + 1465.67$$

*2: This value is calculated and the calculation formula is as below:

$$10.79 = (10.82 + 10.75) / 2$$


*3: This value is calculated and the calculation formula is as below:

$$135.9 = 1465.67 / 10.79$$

$$137.3 = 1481.05 / 10.79$$



Photo Document



****End of test report****