

# LED Incandescent Elevator Series



Stock No.	Product Description
LED-4301	1383-12-2-30-SW (Soft White)
LED-4302	1383-12-2-30-DL (Daylight)
LED-4305	GBF-12-2-30-SW (Soft White)
LED-4306	GBF-12-2-30-DL (Daylight)

**Description:**

Fully encapsulated, 12 Volt, 2 Watt, bayonet base mounting that integrates energy saving LED technology into a 1383 or GBF format. Available in Soft White (SW) or Daylight (DL).

- BA15S or BA15D bayonet base configuration
- 2 Watt, 12V operation (operates on a 9-18V current)
- Soft White SW (3000K)
- Daylight DL (5000K)
- 30 on-board LED diodes
- Up to 50,000 hour lamp life
- Very low heat output
- Not dimmable
- 2 year warranty



**Applications:**

The 2W LED bulb has been designed to retrofit existing incandescent bulb installations, thereby reducing maintenance and energy expenditures - and as an energy saving light source for new fixtures and installations.

- Retail display applications
- Task lighting
- Recessed downlighting
- Hospitality and institutional
- Elevator applications

**Packaging:**

Sub pack: 8 each  
 Master pack: 40 each



**Technical Specifications:**

Bulb Type:	Bayonet base	Base Type:	BA15S / BA15D
Bulb Material:	Glass / Aluminum	Replaces:	15W
Lumens:	60(SW) / 90(DL)	Life Time:	Up to 50,000 hrs.
Input Voltage:	12V DC	Output Power:	2W
Dimensions:	1-3/8" x 1-3/4"	Kelvin Temp:	(SW) est. 3000K
Light Source:	30 pc. LED		(DL) est. 5000K
Beam Angle:	30°	Lumens / Watt:	30(SW) / 45(DL)
UV / IR Radiation:	No	Inert Gasses:	No

Note: All specification information falls within a ± 2% range



**Light Emitting Designs**  
 Environmental Lighting Solutions  
a division of TADD, LLC

NOTE: Light Emitting Designs is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Emitting Designs protects its proprietary information vigorously in the courts of the United States of America.

108 S. Wynstone Park Drive • Suite 103 • N. Barrington, IL 60010 • (847) 380-3540  
 FAX: (847) 380-3542 www.led-llc.com Specs subject to change without notice. 061610\_LED-4301-4306