



IESNA
SUSTAINING
MEMBER

Ref. No.: LCSP#64100069
Date of issue: Nov 28, 2014
Version: 1.1
Total pages: 11



Test report of

IES LM-79-08

Approved Method: Electrical and Photometric

Measurements of Solid-State Lighting Products

Rendered to:

LIGHT EFFICIENT DESIGN, DIV OF TADD LLC
188 S. Northwest Highway Cary, IL60013

For products:

LED Lamp

Models:

LED-8032M57, LED-8032M57C

Test date: Oct 21, 2014 to Nov 22, 2014
Test laboratory: LCTECH (Zhongshan) Testing Service Co.,Ltd
2/F., Technology and Enterprise Development Center, Guangyuan Road,
Xiaolan, Zhongshan, Guangdong, China
Laboratory note: N/A

Complied by:

Lin Qiu
Test Engineer

Nov 28, 2014

Reviewed by:

Richard Li
Technical Manager

Nov 28, 2014

The duplication of this report or parts of it and its use for advertising purposes is only allowed with permission of the testing laboratory. This report contains the result of the examination of the product sample submitted by the applicant. A general statement concerning the quality of the products from the series manufacture cannot be derived therefore. This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Table of Contents

1 General	3
1.1 Product Information	3
1.2 Standards or methods	4
1.3 Equipment list.....	4
2 Test conducted and method	5
2.1 Ambient Condition	5
2.2 Power Supply Characteristics.....	5
2.3 Seasoning and Stabilization	5
2.4 Electrical Instrumentation.....	5
2.5 Color Measurement Method	5
2.6 Total Luminous Flux Measurement Method.....	5
2.7 Luminous Intensity Distribution Measurement Method	5
2.8 Spatial Non-uniformity of Chromaticity.....	5
3 Test Result Summary	6
3.1 Electrical data.....	6
3.2 Photometric data.....	6
4 Test Data	7
4.1 Spectral Distribution	7
4.2 Chromaticity Diagram (CIE 1931).....	7
4.3 ANSI Chromaticity Quadrangles Diagram.....	8
4.4 Color Rendering Details	8
4.5 Goniometry Test Data.....	9
4.6 Zonal Lumen Summary	9
4.7 Polar Curves.....	10
4.8 Candela Tabulation	11

1 General


1.1 Product Information

Brand Name	Light Efficient Design
Trade Mark	-
Luminaire Type	LED Lamp
Model Number	LED-8032M57, LED-8032M57C
Rated Inputs	120-347VAC,50/60Hz
Rated Power	150 W
Rated Initial Lamp Lumens	14000 lm
Declared CCT	5700 K
Power Supply	Integral LED driver
Date of Receipt Samples	Oct 7, 2014
Quantity of Receipt Samples	1 unit

Photo



Picture 1



Picture 2



LCTECH



1.2 Standards or methods

The following standards are partly or totally used or referenced for test:

No.	Name
ANSI/NEMA/ ANSLG C78.377-2011	Specifications for the Chromaticity of Solid State Lighting Products
ANSI C82.77-2002	Harmonic Emission Limits—Related Power Quality Requirements for Lighting Equipment
CIE Pub. No. 13.3-1995	Method of Measuring and Specifying Color Rendering of Light Sources
CIE Pub. No. 15:2004	Colorimetry
IES LM-79-08	Electrical and Photometric Measurements of Solid-State Lighting Products

1.3 Equipment list

ID	Instrument	Model name	Cal. date	Next cal. Date
AC Power supply	LC-I-923	CHP-500	2014-03-04	2015-03-03
AC Power supply	LC-I-953	APW-110N	2014-03-04	2015-03-03
Power analyzer	LC-I-928	WT210	2014-03-21	2015-03-20
Power analyzer	LC-I-954	WT210	2014-03-04	2015-03-03
Photometric colorimetric electric system (2 meter sphere)	LC-I-900	SPR3000	Before use	Before use
Standard lamp	LC-I-971	STD-ESN	2014-05-16	2015-05-15
Goniophotometer(with mirror)	LC-I-902	GMS2000	2014-05-14	2015-05-13
Wireless temperature transmitter	LC-I-958	DWRP-B(0)	2014-08-19	2015-08-18
Wireless temperature transmitter	LC-I-959	DWRP-B(0)	2014-08-19	2015-08-18

2 Test conducted and method

2.1 Ambient Condition

The ambient temperature in which measurements are being taken was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, the air flow around the sample(s) being tested did not affect the performance.

2.2 Power Supply Characteristics

The AC power supply had a sinusoidal voltage wave shape at the prescribed frequency (60 Hz) such that the RMS summation of the harmonic components does not exceed 3 percent of the fundamental during operation of the test item.

The voltage of AC power supply (RMS voltage) applied to the device under test was regulated to within ± 0.2 percent under load.

2.3 Seasoning and Stabilization

No seasoning was performed in accordance with IESNA LM-79-08. And before the measurement, the sample was stabilized until the light output and power variations were less than 0.5% in 30 minutes intervals (3 readings, 15 minutes apart).

2.4 Electrical Instrumentation

The calibration uncertainties of the instruments for AC voltage and current were less than 0.2 percent, and the calibration uncertainty of the AC power meter was less than 0.5 percent (95 % confidence interval, $k=2$).

2.5 Color Measurement Method

Spectral radiant flux was measured by a sphere (2 meter)-spectroradiometer system, and the color characteristics (Color rendering index, correlated color temperature, chromaticity coordinate) were calculated from these by software automatically.

2.6 Total Luminous Flux Measurement Method

Total luminous flux was measured by both sphere-spectroradiometer system and goniophotometer.

Spectral radiant flux was measured by a sphere (2 meter)-spectroradiometer system, and the total luminous flux was calculated from these by software automatically.

Light intensity distribution was measured by a type C goniophotometer (with mirror) which can keep the sample in burn position when the tests conduct, and the total luminous flux was calculated from the intensity data by software automatically.

2.7 Luminous Intensity Distribution Measurement Method

Luminous intensity distribution was measured by a mirror-type goniophotometer (Type C) which can keep the sample in burn position when the tests conduct, and the kinds of graph were generated by software automatically.

2.8 Spatial Non-uniformity of Chromaticity

The customer did not require this measurement.

3 Test Result Summary

3.1 Electrical data

Criteria Item	Result (Sphere)	Result (Goniophotometer)
Input Voltage	277.03 V~60Hz	276.96 V~60Hz
Input Current	0.558 A	0.559 A
Total Power	148.82 W	149.00 W
Power Factor	0.963	0.962
I-THD	19.03%	-


3.2 Photometric data

Criteria Item	Result (Sphere)	Result (Goniophotometer)
Total Lumens	14149.08 lm	14157.93 lm
Luminaire Efficacy	95.08 lm/W	95.02 lm/W
Correlated Color Temperature (CCT)	5402 K	-
Color Rendering Index (CRI)	86.3	-
R9	34	-
Chromaticity Coordinate (x,y)	x= 0.3346 y= 0.3380	-
Chromaticity Coordinate (u,v)	u= 0.2096 v= 0.3175	-
Chromaticity Coordinate (u',v')	u'= 0.2096 v'= 0.4763	-
Duv	-0.0026	-
Spacing Criteria (0-180)	-	1.34
Spacing Criteria (90-270)	-	1.34
Zonal Lumen between 0-60°	-	83.20%


Note: N.A.

4 Test Data

4.1 Spectral Distribution




4.2 Chromaticity Diagram (CIE 1931)





4.3 ANSI Chromaticity Quadrangles Diagram



4.4 Color Rendering Details

R1	R2	R3	R4	R5
86	90	90	87	87
R6	R7	R8	R9	R10
84	89	77	34	74
R11	R12	R13	R14	R15
87	68	87	94	84



LCTECH



4.5 Goniometry Test Data

CIE Type	Direct	Basic Luminous Shape	Circular w/ Sides
Spacing Criteria (0-180)	1.34	Luminous Length	0.21 m (Diameter)
Spacing Criteria (90-270)	1.34	Luminous Width	0.21 m (Diameter)
Spacing Criteria (Diagonal)	1.36	Luminous Height	0.06m
Test Distance	18.35 m		

4.6 Zonal Lumen Summary


Zone	Lumens	%Lamp	%Fixt
0-30	4508.24	31.8	31.8
0-40	7230.12	51.1	51.1
0-60	11779.08	83.2	83.2
0-90	13915.53	98.3	98.3
90-120	160.96	1.1	1.1
90-130	192.87	1.4	1.4
90-150	227.95	1.6	1.6
90-180	242.25	1.7	1.7
0-180	14157.78	100	100

Zone	Lumens
0-10	524.54
10-20	1604.44
20-30	2379.26
30-40	2721.88
40-50	2591.13
50-60	1957.83
60-70	1206.84
70-80	666.26
80-90	263.35
90-100	68.23
100-110	51.03
110-120	41.7
120-130	31.91
130-140	21.66
140-150	13.42
150-160	8.03
160-170	4.62
170-180	1.66



LCTECH

4.7 Polar Curves



Maximum Candela = 5798.7 Located At Horizontal Angle = 90, Vertical Angle = 15

1 - Vertical Plane Through Horizontal Angles (0 - 180)

2 - Vertical Plane Through Horizontal Angles (90 - 270)



LCTECH



4.8 Candela Tabulation

	<u>0</u>	<u>15</u>	<u>30</u>	<u>45</u>	<u>60</u>	<u>75</u>	<u>90</u>
0	5200.49	5200.49	5200.49	5200.49	5200.49	5200.49	5200.49
5	5410.96	5416.18	5419.63	5425.53	5430.91	5436.64	5423.76
10	5676.97	5673.77	5685.64	5683.03	5695.66	5699.2	5703.24
15	5747.52	5751.64	5739.44	5762.25	5770.58	5791.12	5798.7
20	5451.03	5468.46	5466.69	5440.68	5461.22	5458.52	5479.65
25	5123.4	5153.54	5167.6	5131.31	5124.07	5140.91	5145.79
30	4850.99	4864.38	4862.27	4883.74	4866.73	4890.56	4878.1
35	4344.56	4332.86	4303.23	4351.89	4304.83	4349.19	4316.78
40	3867.59	3903.96	3866.67	3859.93	3853.79	3848.74	3840.99
45	3382.04	3346.52	3420.6	3341.21	3365.88	3362.17	3359.14
50	2817.02	2810.2	2851.28	2832.43	2824.34	2814.83	2854.73
55	2146.27	2164.79	2158.47	2162.68	2161.59	2169.25	2170.85
60	1590.17	1610.29	1622.16	1612.9	1598.76	1620.9	1634.62
65	1184.09	1196.96	1200.75	1199.99	1201.43	1197.89	1214.22
70	862.01	866.39	865.38	867.99	867.40	867.06	871.27
75	617.75	617.48	617.62	623.00	617.76	620.23	617.58
80	418.92	418.72	422.33	421.52	418.39	416.96	421.12
85	229.90	232.80	234.06	234.13	233.91	233.11	232.52
90	78.20	78.61	78.57	80.62	80.91	82.41	88.31
95	58.35	58.43	58.33	58.51	58.60	58.72	58.41
100	52.14	52.25	52.11	52.20	52.44	52.58	52.45
105	47.53	47.64	47.61	47.71	47.90	48.11	47.97
110	45.00	44.99	44.87	44.87	45.02	45.03	45.02
115	42.16	42.12	42.00	41.97	42.08	42.19	42.06
120	38.91	38.76	38.77	38.70	38.84	38.85	38.91
125	35.59	35.54	35.47	35.48	35.63	35.69	35.59
130	32.02	32.07	32.06	32.12	32.14	32.25	31.99
135	27.83	27.77	27.70	27.75	27.79	27.86	27.78
140	23.96	23.90	23.80	23.78	23.88	23.93	23.87
145	21.26	21.14	21.16	21.15	21.21	21.27	21.05
150	18.86	18.81	18.89	18.91	19.01	19.00	18.92
155	16.82	16.84	16.94	16.92	16.95	17.06	16.94
160	16.23	16.22	16.29	16.35	16.35	16.50	16.30
165	16.05	16.02	16.10	16.23	16.22	16.32	16.21
170	16.55	16.48	16.55	16.57	16.62	16.56	16.55
175	17.71	17.70	17.70	17.68	17.63	17.71	17.63
180	18.44	18.44	18.44	18.44	18.44	18.44	18.44

****End of test report****