

In Situ Temperature Measurement Test Report

For

LIGHT EFFICIENT DESIGN

(Brand Name: N/A)

188 S. Northwest Highway Cary, IL 60013

LED Luminaires

Model name(s): LED-8038E30-A
LED-8038-NW-E27-A

Remark: The two models are the same product with two model names

Representative (Tested) Model: LED-8038E30-A

Model Different: All construction and rating are the same, except CCT

Test & Report By:

Review By:

Engineer: Garman Mo

Manager: Tommy Liang

Date: Apr.19,2017

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Laboratory: Standard-Tech Co. Ltd Testing Center

NVLAP CODE: 201011-0

Report Format Number STD/QR4918-A/0

Address: Standard-Tech Building, No.6 Guanhong Road, Guangzhou Science City, Guangzhou 510663, China

Tel: 8620-3229 0320

Fax: 8620-32290422

<http://www.standard-tech.com>

Table of Contents

1 General	3
1.1 Product Information	3
1.2 Standards or methods	4
1.3 Equipment list	4
2 Test conducted and method	4
2.1 Ambient Condition	4
2.2 Temperature Stabilization	4
2.3 Thermocouples	5
2.4 Thermocouples contact	5
3 Test Results	6
3.1 Data:	6
3.2 Test Photo:	6


DRAFT

1 General

1.1 Product Information

Brand Name	N/A
Model Number	LED-8038E30-A;LED-8038-NW-E27-A
Luminaire Type	LED Luminaires
Nominal Power	14W
Rated Initial Lamp Lumen	--
Declared CCT	3000K
LED Manufacturer	Edison Opto Corporation
LED Model	2T03X5WW11000003
Sample Receipt Date	Jan 16,2017
Sample Number	GZE161214-AP1

Photo



1.2 Standards or methods

The following standards are partly or totally used or referenced for test:

No.	Name
ANSI/UL 1598:2008	Luminaires

1.3 Equipment list

Equipment ID	Equipment Name	Last Calibration Date	Next Calibration Date
ST-R-049	Power Meter	2016-07-07	2017-07-06
ST-R-401	Temperature Tester	2017-01-29	2018-01-28

2 Test conducted and method

2.1 Ambient Condition

Test was conducted in an ambient temperature of $25 \pm 5^{\circ}\text{C}$. Ambient temperature variations above or below 25°C was subtracted from or added to temperatures recorded at points on the luminaire.

The ambient temperature was measured by a thermocouple which was immersed in 15ml of mineral oil in a glass container.

2.2 Temperature Stabilization

Temperatures were measured after they have stabilized when the test has been running for a minimum of 7.5 hours, or the test has been running for a minimum of 3 hours and three successive reading taken at 15 minutes intervals are with 1°C of another and are not rising.

2.3 Thermocouples

Type J thermocouple was used for temperature measurement. The thermocouple was 0.05mm²(30AWG), and complied with the requirements specified in ASTM MNL 12 and limits of error specified in NIST ITS 90 and ISA MC96.1.

2.4 Thermocouples contact

Thermocouples were in contact with the TMP LED location described in LM-80 test report. In order to gain the maximum temperature, if appropriate, more than one thermocouple were contact in these locations. For details information, please refer to clause 3.3 for the photo of thermocouple contact.

DRAFT

3 Test Results

Test date	2017-01-17	Test Ambient	25.1 °C
Sample No.		LED Package Model	
GZE161214-API		2T03X5WW11000003	
LED driver of Each Lamp	Output voltage V	Measured LED working current (Max.) mA	
1	30.1	40.2	

3.1 Test Data:


Input Vol.	120.0V	Input Current	0.1083A	Input Wattage	12.75W	Temperature stabilization time:	500 min	
No.	Temperature (°C)		No.	Temperature (°C)		No.	Temperature (°C)	
	Measured	Corrected at 25°C		Measured	Corrected at 25°C		Measured	Corrected at 25°C
1	60.6	60.5	3	59.7	59.6	5	61.4	61.3
2	61.9	61.8	4	60.2	60.1	6	59.1	59.0
The highest in-situ measured temperature LED is 61.8°C								

3.2 Test Photo:

Ts Position:



Thermocouple Location on Temperature Measurement Point (TMP):



Results

Time (t) at which to estimate lumen maintenance (hours):	50,000
Lumen maintenance at time (t) (%):	74.35%
Reported L70 (hours):	59,000

***** END OF THE TEST REPORT*****

Laboratory: Standard-Tech Co. Ltd Testing Center
NVLAP CODE: 201011-0

Report Format Number STD/QR4918-A/0

Address: Standard-Tech Building, No.6 Guanhong Road, Guangzhou Science City, Guangzhou 510663, China

Tel: 8620-3229 0320

Fax: 8620-32290422

<http://www.standard-tech.com>