## LED-8088M 50W LED METAL HALIDE BALLAST COMPATIBLE SHOEBOX/WALLPACK

LED-

8088M57-



## Models

LED-8088MXX-MHBC, 4000K or 5700K CCT, E39

## **Features**

- 50 Watt LED Replaces existing 150w or 175w Metal Halide Lamp
- Operates with pulse start and probe start magnetic 150W & 175W Metal Halide Ballasts only
- · Optimized for Shoebox/ Wallpack HID Fixtures
- Type V Optics
- UL Component approved for damp environments (USA & Can)
- Advanced active cooling, Sunon Mag-lev >70,000 hr. fan with temperature control ensures long LED life

LED-

8088M40-

E39 Mogul Base


Models US/CAN

- >50,000 rated LED life
- 5 year limited warranty (see website for details)


**Technical Specifications** 

• Rated for enclosed fixture





## **Lux Distance Curve**



| МНВС   | мнвс   |  |
|--|--|--|
| 4000K  | 5700K  |  |
| 50 watts                                     |  |  |
| 77.8   |  |  |
| 124  |  |  |
| 150W & 175W MH                               |  |  |
| E39  |  |  |
| 150W & 175W Pulse or<br>Probe Start Ballasts |  |  |
| 2835   |  |  |
| Type V                                       |  |  |
| No   |  |  |
| -40°F - +122°F                               |  |  |
| Up to 50,000 Hrs.                            |  |  |
| 5 Year Limited*                              |  |  |
|  |  |  |
| Yes  | Yes  |  |
| 77.8   | 77.8   |  |
| 3947   | 5826   |  |
| 6079   | 5984   |  |
| 116  | 115  |  |
| 42.06%                                       | 41.81%   |  |
| 0.688  | 0.684  |  |
| 87.1   | 85   |  |
|  | 4000K 50 v 77 1: 150W & 17: Probe Sta 28 Typ N -40°F - Up to 50 5 Year I Yes 77.8 3947 6079 116 42.06% 0.688 |  |

26

0.00124

23

0.00145

9 / Master Carton

5.3"x 4.7"x 10.1" 1.8lbs.

16.7"x 15" x 10.8" 13.8 lbs.

| LED Power<br>Consumpti<br>on<br>(Watts) | HID<br>Power<br>Consumpti<br>on<br>(Watts) | HID<br>Ballast<br>Power<br>Consumpti<br>on<br>(Watts) | Total<br>Savings<br>(Watts) | Annual<br>Energy<br>Savings<br>(14<br>hrs/day) | Lifetime<br>Energy<br>Savings<br>(over<br>50,000 hrs) |
|---|--|---|-----------------------------|--|---|
| 77.8                                    | 250  | 37.5  | 172.2                       | \$97   | \$947.10  |

| Mounting Orientation |              | Minimum Fixture Size |                       |       |
|----------------------|--------------|----------------------|-----------------------|-------|
| Base Up              | Base<br>Down | Horiz                | Requirements (inches) |       |
|                      |              | <b>4</b>             | Length                | 9.7   |
| 11. III              |              |                      | Width                 | 5.7   |
|                      | 11           |                      | Height                | 5.7   |
|                      |              |                      | Cu. Inches            | 315.2 |
| Approved             | Approved     | Approved             | cu. Iliciles          | 315.2 |



R9

Duv

Unit

Master

**Packaging** 

