



## LED TEMPORARY WORK SITE LIGHTS

### Models

LED-9006-50K	60W Work Light with 20' power cord
LED-9010-50K	100W Work Light with 35' power cord
LED-9015-50K	150W Work Light with 35' power cord

### Features

- Work Lights are easy to install and offer a flexible solution for temporary lighting
- Operates on 120/277 volt power, and includes a 20' to 35' long power cord. Operates on 277VAC with jumper cable.
- Lamps can easily be daisy chained to cover large areas  
Up to 10 of the LED-9006 fixtures or up to 6 of the LED-9010 fixtures or a combination of the two, not exceeding 600W
- Includes remote control
- IP 64 rated - suitable for damp locations
- 5 Year Warranty



### TECHNICAL SPECIFICATIONS

MODEL	VOLTAGE	WATTAGE	LUMENS	LPW	REPLACES	BASE	CCT	CRI*	THD*	PF*	R9*	Duv*	LIGHT DISTRIBUTION	DIMMABLE
LED-9006-50K	120/277VAC	60W	6,600	110	250W HID	20' power cord	5000K	>80	<20%	>0.9	N/A	N/A	360°	NO
LED-9010-50K	120/277VAC	100W	11,000	110	400W HID	35' power cord	5000K	>80	<20%	>0.9	N/A	N/A	360°	NO
LED-9015-50K	120/277VAC	150W	16,500	110	600W HID	35' power cord	5000K	>80	<20%	>0.9	N/A	N/A	360°	NO

### PACKAGING SPECIFICATIONS

MODEL	PRODUCT DIMENSION	PRODUCT WEIGHT	UNIT CARTON DIMENSION	UNIT CTN WT	SHIPPER CARTON DIMENSION	SHIPPER CTN WT	CARTON QUANTITY
LED-9006-50K	6.5" dia. X 10.8" tall	4.0 lbs	12.8" x 8.5" x 8.2"	4.0 lbs	17.5" x 13.4" x 17.3"	16.5 lb	4
LED-9010-50K	6.5" dia. X 12.2" tall	4.2 lbs	14.5" x 8.5" x 8.2"	4.2 lbs	17.5" x 15.0" x 17.3"	17.3 lb	4
LED-9015-50K	6.5" dia. X 13.7" tall	4.4 lbs	15.5" x 8.5" x 8.2"	4.4 lbs	17.5" x 16.1" x 17.3"	18.1 lb	4

### UPC / UCC

### DESIGN LIGHTS CONSORTIUM QPL CERTIFICATION SUMMARY

MODEL	PRODUCT UPC	CARTON UCC	QPL CATEGORY 1	PRODUCT CODE	FAMILY CODE	QPL CATEGORY 2	PRODUCT CODE	FAMILY CODE
LED-9006-50K	8440060 9103 3	10 8440060 9103 0	N/A	N/A	N/A	N/A	N/A	N/A
LED-9010-50K	8440060 9104 0	10 8440060 9104 7	N/A	N/A	N/A	N/A	N/A	N/A
LED-9015-50K	8440060 9105 7	10 8440060 9105 4	N/A	N/A	N/A	N/A	N/A	N/A




### ENERGY SAVINGS VS. HID

	LED-9006-50K	LED-9010-50K
LED Lamp Power (watts)	60	100
HID Lamp Power (watts)	250	400
HID Ballast Power (watts)	37.5	60
Total power Savings (watts)	227.5	360
Annual Energy Savings	\$128	\$202
Lifetime Energy Savings over 50,000 hrs)	\$1,251	\$1,980

### NOTES

Specifications are subject to change without notice.

### Mounting Orientation

BASE DOWN	BASE UP	HORIZONTAL	
			
NOT APPROVED	APPROVED	NOT APPROVED	
Recommended Minimum Fixture Size			
Width	N/A	THERMAL SPECIFICATIONS	
Height	N/A	OPERATING TEMPERATURE	-40°F to +122°F
Volume (Cu. In.)	N/A	IN-SITU TEMP MEASUREMENT/L70	
		LED TEMPERATURE*	N/A
		L70 LED LUMEN MAINTAINENCE*	>50,000